

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number  
WO 2004/036568 A1

- (51) International Patent Classification<sup>7</sup>: **G11B 7/14**
- (21) International Application Number:  
PCT/IB2003/004022
- (22) International Filing Date:  
15 September 2003 (15.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
02079280.0 16 October 2002 (16.10.2002) EP
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GOOSSENS, Hendrik, J.** [NL/CN]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **TUKKER, Teunis, W.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: **DEGUELLE, Wilhelmus, H., G.**; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

(54) Title: OPTICAL SCANNING DEVICE



(57) Abstract: An optical head for use in the scanning of a record carrier, the record carrier having data stored on data tracks therein on a plurality of information layers (3, 4) at a plurality of depths within the record carrier. The optical head comprises: a movable optical element (16) arranged in an optical path to act upon a first radiation beam (12) and a second radiation beam (14) to provide the beams with a different displacement perpendicular to the optical path; and a lens system for focusing said first beam (12) at a first focal point (A) on a first information layer (3) of the record carrier and the focusing of the second beam (14) at a second different focal point (B) on a second information layer (4), wherein a spacing, transverse to the data tracks, between said first and second focal points (A, B) is controllable by varying the configuration of the movable optical element.

WO 2004/036568 A1



DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT,  
RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

**Published:**

— with international search report

BEST AVAILABLE COPY

## Optical scanning device

This invention relates to an optical scanning device and an optical head for use therein, for scanning an optical record carrier. In particular, but not exclusively, the invention relates to a device for the simultaneous scanning of two different information layers of a multi-layer record carrier.

5 EP-A-0837455 describes an optical scanning device for scanning simultaneously at least two information layers and with partial beams which differ in terms of polarization direction and propagation behavior. The device includes a radiation source for supplying an input radiation beam, a polarizing prism-type beam splitter, and a birefringent collimator lens for producing two different beams which are projected through an objective  
10 lens to scan the different information layers. The birefringent lens provides a wavefront difference between the beams to read different information layers, but does not allow for variations in the spacing between the different information layers, or variations in the position of tracks within the different information layers.

JP-A-10149560 describes an optical scanning device for scanning  
15 simultaneously at least two information layers. The device includes a radiation source for supplying one radiation beam, one beam splitter, one collimator lens, a polarizability element having an optically uniaxial birefringence (for transforming the radiation beam into two radiation beams which differ in terms of polarization direction and propagation behavior), and one objective lens. Again, the wavefront difference between the beams is fixed.

20 JP-A-2000195097 describes optical scanning (reading or writing) devices for scanning a plurality of information layers. In one embodiment, the device includes one objective lens and a plurality of radiation sources and associated beam splitters for coupling a first partial beam with a plurality of partial beams which are used to scan different information layers. Each of the plurality of partial beams passes through a separately  
25 movable element to modify the scanning characteristics of the beams for the different layers. In another embodiment, the device includes a plurality of objective lenses and a single radiation source producing a beam which is split towards the different objective lenses by polarizing optics. Each of the different objective lenses is separately movable to modify the scanning characteristics of the beams for the different layers.

BEST AVAILABLE COPY

In accordance with the present invention there is provided an optical head for use in scanning a record carrier, the record carrier having data stored on data tracks therein on a plurality of information layers at a plurality of depths within the record carrier, wherein the optical head comprises:

- 5                   - a movable optical element arranged in an optical path to act upon a first radiation beam and a second radiation beam to provide the beams with a different displacement perpendicular to the optical path; and
- a lens system for focusing said first beam at a first focal point on a first information layer of the record carrier and the focusing of the second beam at a second
- 10               different focal point on a second information layer,
- wherein a spacing, transverse to the data tracks, between said first and second focal points is controllable by varying the configuration of the movable optical element.

Such an arrangement allows for the simultaneous read out of two information

15   layers of a multi-layer record carrier, and allows for variations in a transverse spacing between the data tracks of the information layers, for example due to an eccentricity of one or both layers of the record carrier being read to be accommodated using a common optical path for both scanning beams.

20

Further features and advantages of the invention will become apparent from the following description of preferred embodiments of the invention, given by way of example only, made with reference to the accompanying drawings wherein:

Fig. 1 shows a cross-section schematic view of a dual-layer optical disk OD in

25   accordance with an embodiment of the present invention.

Fig. 2 shows a schematic illustration of components of an optical scanning device for scanning a dual-layer optical disk OD, in accordance with an embodiment of the present invention.

Figs. 3, 4 and 5 illustrate a movable optical element in different rotational configurations, as

30   according to an embodiment of the present invention.

Fig. 6 shows schematically the radial tracking of radiation beams in accordance with an embodiment of the present invention.



Fig. 1 shows a cross-section schematic view of a dual-layer optical disk OD in accordance with an embodiment of the present invention. The optical disk OD comprises a substrate 1 and a transparent layer 2, between which at least one information layer 3 is arranged. In the case of a dual-layer optical disk, as illustrated, two information layers 3, 4 are arranged behind the transparent layer 2, at different depths within the disk. A further transparent layer 5 separates the two information layers. The transparent layer 2 has the function of protecting the uppermost information layer 3, while mechanical support is provided by the substrate 1.

Information may be stored in the information layers 3, 4 of the optical disk in the form of optically detectable marks arranged in substantially parallel, concentric or spiral tracks, not indicated in Fig. 9. The marks may be in any optically readable form, e.g. in the form of pits, or areas with a reflection coefficient or a direction of magnetization different from their surroundings, or a combination of these forms.

Fig. 2 shows a schematic illustration of components of an optical head for scanning a dual-layer optical disk OD, according to an embodiment of the present invention. The dual-layer optical disk OD in Fig. 2 is as described for Fig. 1 and the same reference labels are included therein.

The scanning device includes an optical pickup unit (OPU) mounted on a radially-movable arm. The OPU includes all components illustrated in Fig. 2, other than the disk OD. A radiation source 6, for example a single semi-conductor laser, emits a radiation beam 7 of a predetermined frequency, for example 650 nm, with an optical axis 8. The radiation beam is collimated by a fixed collimator lens 9 to a collimated beam.

The radiation beam 7, in its collimated state, passes through a birefringent lens element. In this embodiment, the birefringent lens element is a passive liquid crystal lens 10. The radiation beam 7 is modified by the liquid crystal lens 10 to a first and second polarized beam 12, 14 respectively. The first and second polarized beams 12, 14 are orthogonally polarized with respect to each other and each have a different vergence. Both polarized beams 12, 14 follow the optical axis 8.

A movable optical element 16, positioned on the optical axis 8, has variable rotational configuration states by rotation 18 about the optical axis. In this embodiment, the movable optical element is a Wollaston prism 16, which includes a birefringent prism. The Wollaston prism separates the polarized beams 12, 14 following the optical axis 8 such that the polarized beams 12, 14 are both differently displaced perpendicular to the optical axis 8. The polarized beams 12, 14 are reflected by a folding mirror 20 to an objective lens 22 which

focuses the first polarized beam 12 to a first spot A on the first information layer 3 of the optical disk OD. The objective lens 22 additionally focuses the second polarized beam 14 to a different spot B on the second information layer 4 of the disk OD. Both polarized beams 12, 14 are reflected by the first and second information layers 3, 4 respectively, of the disk OD and follow a common optical reverse beam path, the direction of which is altered by a beam director 24. The first and second polarized light beams 12, 14, following the common reverse beam path are split by a polarization dependent beam splitter 26 such that each polarized beam, 12, 14 is differently directed at a desired part of a detector system 28.

The detector system 28 includes a data detecting circuit for detecting a data signal corresponding to information read out from the first and second information layers 3, 4, and tracking and focus error detection circuits for detecting focus and tracking errors due to axial displacement of the beam spots, relative to the first and second information layers 3, 4, including a signal indicating mutual displacement of the beam spots in the radial direction, i.e. in the direction transverse to the data tracks in the two information layers 3, 4.

A data signal from the detector system 28 corresponding to detected mutual transverse displacement of the beams is used to vary the rotational configurations of the Wollaston prism 16 in a closed-loop servo system.

Figs. 3, 4 and 5 show the Wollaston prism 16 as described and illustrated in Fig. 2 in different rotational configurations in accordance with an embodiment of the present invention. As shown in Fig. 3, the Wollaston prism 16 lies in a first rotational configuration and the orthogonally polarized first and second light beams 12, 14 following a common optical axis, are radially displaced by the Wollaston prism. As a result of this first rotational configuration of the Wollaston prism 16, the displacement between the first spot A of the first beam 12 on the first information layer 3 and the second spot B of the second beam 14 on the second information layer 4 describe the radial displacement line 30.

Referring now also to Fig. 6, the tracking paths of beams 12, 14 whilst reading both information layers 3, 4 are shown showing variations of radial spacing between the tracking paths. The uppermost tracking path 32 of the first spot A on the first information layer 3 lies above a different tracking path 34 of the second spot B on the second information layer 4. The radial displacement line 30 is shown and corresponds to the first rotational configuration of the Wollaston prism shown in Fig. 3.

Fig. 4 shows a second rotational configuration of the Wollaston prism 16. In this configuration the prism is rotated by an angle of  $+90^\circ$  about the rotational axis from the first rotational configuration. Consequently, displacement between the first spot A and



second spot B now describes a second radial displacement line 36. In Fig. 6 this second radial displacement line 36 is illustrated and lies at the angle of  $90^\circ$  to the first radial displacement line 30.

Referring now to Fig. 5, a third rotational configuration of the Wollaston prism 16 is shown. In this configuration the Wollaston prism is rotated by an angle of  $-90^\circ$  from the first rotational configuration about the rotational axis. As a result, displacement between the first spot A and the second spot B now describes a third radial displacement line 38. In Fig. 6, this third radial displacement line 38 is illustrated lying at the angle of  $-90^\circ$  to the first radial displacement line 30.

In this described manner, and by varying rotational configurations of the Wollaston prism 16 by differently varying the angle of rotation about the rotational axis, the angle of a radial displacement line can be controlled. Consequently spots A and B can accommodate any variation in radial spacing between the first and second information layers 3, 4 as a result of an eccentricity of the two information layers of the disk OD.

Rotation of the Wollaston prism 16 about the rotational axis as described is achieved by an appropriate mechanical rotation mechanism (not shown).

In this embodiment of the present invention, the liquid crystal lens 10 is of a passive nature and as a result any axial displacement of the first and second beams 14, 12 and focusing at the spots A, B, is achieved by variation in the distance of the objective lens 22 from the information layers 3, 4 of the disk OD using a loop-servo setup between the detector system 28 and mechanical actuators (not shown) controlling the position of the objective lens 22. Variation of the position of the objective lens 22 is achieved using a data signal relating to axial tracking and focus errors from the detector system.

In a further envisaged embodiment of the present invention, the liquid crystal lens 10 includes both a passive and an active element. The active element can be varied by applying a voltage across electrodes in the liquid crystal lens which varies the vergence of the emerging light beams. In this example therefore, variation of the axial displacement of the first and second beam 3, 4 and the focusing at the spots A, B is achieved by a combination of variation of the active liquid crystal lens properties and the distance of the objective lens 22 from the information layers of the disk OD.

The above embodiments are to be understood as illustrative examples of the invention. Further embodiments of the invention are envisaged.

In a further embodiment it is envisaged that the Wollaston prism 16 is placed in the light path between the source 6 and the liquid crystal lens 10.



In another envisaged embodiment, the movable optical element is not limited to comprising a Wollaston prism. Different configuration states of the movable optical element may not necessarily be achieved by mechanical rotation of the element about a rotational axis, but for example by the movement of an appropriately configured birefringent element transverse to the optical axis.

The invention is, in one embodiment, applied to the scanning of dual-layer Digital Versatile Disks (DVDs). However, the optical head of the invention has utility to the scanning of different information layers of other types of multi-layer record carrier.

It is to be understood that further equivalents and modifications not described above may also be employed without departing from the scope of the invention, which is defined in the accompanying claims.





## CLAIMS:

1. An optical head for use in scanning a record carrier, the record carrier having data stored on data tracks therein on a plurality of information layers at a plurality of depths within the record carrier, wherein the optical head comprises:
  - a movable optical element (16) arranged in an optical path to act upon a first radiation beam (12) and a second radiation beam (14) to provide the beams with a different displacement perpendicular to the optical path; and
  - a lens system for focusing said first beam (12) at a first focal point (A) on a first information layer (3) of the record carrier and the focusing of the second beam (14) at a second different focal point (B) on a second information layer (4),
  - wherein a spacing, transverse to the data tracks, between said first and second focal points (A, B) is controllable by varying the configuration of the movable optical element (16).
2. An optical head according to claim 1, wherein the head is adapted to scan different information layers (3, 4) of the record carrier simultaneously using the first and second beams (12, 14).
3. An optical head according to claim 1 or 2, wherein the movable optical element (16) is adapted to be rotated (18) about the optical path to obtain various configuration states.
4. An optical head according to any preceding claim, wherein said movable optical element (16) comprises a polarization dependent optical element.
5. Apparatus according to claim 4, wherein the movable optical element (16) comprises a Wollaston prism.
6. An optical head according to claim 4 or 5, wherein the first beam (12) is substantially orthogonally polarized with respect to the second beam (14).

7. An optical head according to any preceding claim, comprising a birefringent lens element (10) for producing a different depth within the record carrier at which the first and second beams (12, 14) are focused.

5

8. An optical head according to claim 7, wherein the birefringent lens element (10) includes a liquid crystal material.

9. An optical head according to any preceding claim, comprising a detection system (28) for detecting a separate information signal in each of said first and second beams (12, 14) after scanning of the record carrier thereby.

10. An optical head according to claim 9, comprising an optical system adapted such that said first and second beams (12, 14), after having been scanned by the record carrier, follow a common optical path at least part of the way towards said detection system (28).

11. An optical head according to claim 10, wherein the common optical path includes the movable optical element (16).

20

12. An optical head according to claim 10 or 11, wherein the common optical path includes the birefringent lens element (10).

13. An optical head according to any of claims 9 to 12, comprising a beam splitter (26) for separately directing said first and second beams (12, 14) towards different paths of said detection system (28).

14. An optical head according to any of claims 9 to 13, wherein said detection system (28) is arranged to generate a signal which is arranged to vary the configuration of the movable optical element (16), the signal varying the transverse spacing between the first and second focal points (A, B).

30

15. An optical scanning device comprising an optical head according to any of the preceding claims.



1/3




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 2

3/3




FIG. 6

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/03/04022

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B7/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01 93254 A (DAMBACH SOEREN ;RICHTER HARTMUT (DE); THOMSON LICENSING SA (FR)) 6 December 2001 (2001-12-06) page 16, line 18 -page 18, line 30; figures 7,8	1,9,10, 15
Y	EP 0 837 455 A (THOMSON BRANDT GMBH) 22 April 1998 (1998-04-22) cited in the application the whole document	1-15
A	EP 1 014 347 A (THOMSON BRANDT GMBH) 28 June 2000 (2000-06-28) the whole document	1-15
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

15 December 2003

Date of mailing of the international search report

14/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Hermann, R

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP03/04022

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 10, 17 November 2000 (2000-11-17) -& JP 2000 187880 A (SHARP CORP), 4 July 2000 (2000-07-04) abstract; figures 5-14 -----	1-15
A	EP 0 496 132 A (PHILIPS NV) 29 July 1992 (1992-07-29) column 7, line 28 -column 10, line 43; figures 1B,,4A-4D -----	1-15
A	US 4 783 152 A (NISHIMOTO YOSHIFUMI) 8 November 1988 (1988-11-08) column 3, line 26 -column 5, line 27; figures 2-4 -----	1,7,8

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP03/04022

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0193254	A	06-12-2001	AU 7407901 A BR 0111198 A CN 1436348 T WO 0193254 A1 EP 1295286 A1 US 2003165106 A1	11-12-2001 08-04-2003 13-08-2003 06-12-2001 26-03-2003 04-09-2003
EP 0837455	A	22-04-1998	DE 19643105 A1 CN 1180890 A EP 0837455 A2 ID 18591 A JP 10134408 A SG 54568 A1 US 5905708 A	23-04-1998 06-05-1998 22-04-1998 23-04-1998 22-05-1998 16-11-1998 18-05-1999
EP 1014347	A	28-06-2000	DE 19859035 A1 CN 1258068 A EP 1014347 A2 JP 2000195097 A KR 2000047692 A PL 337272 A1 US 2003026189 A1	29-06-2000 28-06-2000 28-06-2000 14-07-2000 25-07-2000 03-07-2000 06-02-2003
JP 2000187880	A	04-07-2000	NONE	
EP 0496132	A	29-07-1992	NL 9002841 A DE 69125264 D1 DE 69125264 T2 DE 69133021 D1 DE 69133021 T2 EP 1187116 A1 EP 0496132 A2 EP 0756273 A1 JP 2000137927 A JP 3110532 B2 JP 4301226 A KR 246282 B1 KR 254150 B1 US 2003133391 A1 US 5408453 A US 6538978 B1 US 5841753 A	16-07-1992 24-04-1997 04-09-1997 27-06-2002 02-01-2003 13-03-2002 29-07-1992 29-01-1997 16-05-2000 20-11-2000 23-10-1992 15-03-2000 15-04-2000 17-07-2003 18-04-1995 25-03-2003 24-11-1998
US 4783152	A	08-11-1988	JP 61160714 A DE 3600325 A1 FR 2575838 A1 GB 2171811 A	21-07-1986 10-07-1986 11-07-1986 03-09-1986